

Supaflex Glove



PRODUCT DATA SHEET

ITEM CODE: GFN267

Product Overview

- **Liner Material:** Nylon, Spandex/Lycra
- **Dip Material:** PU (Polyurethane), Nitrile
- **Dipping Styles:** Micro foam
- **Touch Screen:** Yes
- **MSDS:** N/A
- **Food Contact:** No
- **Cuff Style:** Knit wrist
- **Gauge:** 15
- **Country of Origin:** China



Applications

- | | |
|---|--|
| <ul style="list-style-type: none">• Handling small metal parts• Handling plastic components• Precision assembly work• General handling• Engineering | <ul style="list-style-type: none">• Assembly and technical work• Automotive industry• Building and construction• Logistics and warehousing• Mining |
|---|--|

Storage

Store in a cool dry area away from direct sunlight.
Cover to keep away from dust.

Size Details

Product	Size	Hem Colour
GFN267-06	XS	Blue
GFN267-07	S	Purple
GFN267-08	M	Green
GFN267-09	L	Brown
GFN267-10	XL	Yellow
GFN267-11	2XL	Grey

Warranty

Limited lifetime – manufacturing defects

Care/Cleaning Instructions

Wash gently by hand or machine using commercial laundry soap or detergent in water temperature not exceeding 30°C. Rinse in cold or warm water. Do not bleach. Allow the glove to dry naturally, avoiding direct sunlight. Do not tumble dry or iron.

Packaging

Hangcard: 1 pair

Carton: 120 pairs

Polybag: 12 pairs

Standards and Certification

EN388:2016



4131X




STANDARD
100



Glove and hand size chart as per standard EN ISO 21240

Glove size	5	6	7	8	9	10	11	12	13
Palm Circumferences	127mm	152mm	178mm	203mm	229mm	254mm	279mm	304mm	329mm
Hand Length	148mm	160mm	171mm	182mm	192mm	204mm	215mm	227mm	237mm
Standard Glove Sizes	XXS/5	XS/6	S/7	M/8	L/9	XL/10	XXL/11	3XL/12	4XL/13
Maxisafe Riggers and Mechanics Glove Sizes	XXS/6	XS/7	S/8	M/9	L/10	XL/11	XXL/12	3XL/13	4XL/14

AS/NZS 2161.3 Occupational protective gloves, Part 3:
Protection against mechanical risk
Based on EN388 – Protective gloves against mechanical risks.



EN388:2016
XXXXXX

Abrasion	1-4
Cut (Coup Test)	1-5
Tear	1-4
Puncture	1-4
Cut (TDM Test ISO 13997)	A-F
Impact Protection	P,F,X

EN388:2016+A1:2018	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance (number of cycles)	100	500	2000	8000	-
Blade cut resistance (index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture resistance (N)	20	60	100	150	-

EN ISO 13997:1999 TDM	Level A	Level B	Level C	Level D	Level E	Level F
Cut resistant test levels (N)	2	5	10	15	22	30

EN388:2016+A1:2018 IMPACT TEST	P (Pass)	F (Fail)	X
Average transmittance force (kg)	≤7kg	≥9kg	Not tested