

Technical Data Sheet

Autoshield Activator Ap1001**Adhesion promoter to enhance adhesion to glass and lacquer of Polyurethane Adhesives**

Adheseal
The Adhesive and Sealant Specialists

Description.

Adhesive wipe especially designed to enhance the adhesion of P.U. adhesives to glass and lacquer.

Application

All surfaces should be dry, clean and free from dust or grease. Wipe the glass with Autoshield Activator AP1001.

Use a clean cloth or tissue use very sparingly. It is recommended that adhesion tests be carried out.

The user should ensure that the product is suitable for their requirements. Ask for advice from our technical service if necessary.

METHOD OF USE

With clean applicator or rag.

APPLICATION TEMPERATURE

Between +5°C and +40°C

CLEANING

wet: & dry

Tools & Surfaces with solvent or alcohol

COLOUR

Clear

Limitations

Do not use if the contents of the container has become milky. If this is the case the Activator has absorbed water and should be disposed of.

Use only in well ventilated spaces. Do not expose to thermal, mechanical or chemical influences before dry.

Shelf life

18 months if kept in the original packing and stored in cool and dry conditions. While the Activator is clear it is still fit for purpose

Packing

250 ml containers
1 Litre containers

Safety


The product should be applied in well-ventilated rooms. The vapours should not be inhaled over long periods of time or in high concentrations. Avoid prolonged contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Avoid contact with food as long as the primer is uncured. Consult our safety data sheet. This product is classified as hazardous according to Work safe Australia. Skin irritation and sensitization may occur in sensitive individuals. Please consult S.D.S. for this product for further information.

Guarantee / Warranty:

We warrant our products to be free of defects and manufactured to rigid quality control specification. As it is impossible to control the use and application of the products, the company's liability is limited to replacing such quantities of product as are proven to be defective. The company disclaims any claims for repainting or other labour resulting from the use of the product. No responsibility is assumed for consequential damages arising from the use of the product. All other warranties including merchantability or fitness for a particular purpose) are excluded. No representative of the company is authorised to grant any warranty or waive this limitation of liability. All claims concerning product defects must be made within twelve months of shipment. Absence of such claim in writing during this period will constitute a waiver of all such claims with respect to such product.

Adequate Tests:

The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendation and suggestion contained herein are made without guarantee or representation as to the results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your require-



Adheseal Pty Ltd, Brisbane , 26 Wolverhampton St, Stafford QLD 4053 PH (07) 3356 0000 Email sales@adheseal.com.au
Adheseal Pty Ltd, Sunshine Coast, 18 Kessling Ave, Kunda Park QLD 4556 PH (07) 5447 0022 Email sc@adheseal.com.au
Adheseal Pty Ltd, Gold Coast, 4/12 Distribution AV Molendinar QLD 4214 PH (07) 5681 1111 Email gc@adheseal.com.au
web: www.adheseal.com.au