

Technical Data Sheet

Gap Filla

Acrylic Gap Sealant

Adheseal
The Adhesive and Sealant Specialists

DESCRIPTION

Adheseal Gap Filla is an acrylic sealant specifically formulated for applications where more rigid fillers may crack and/or fall out.

TYPICAL USES

Joint sealer for window and door frames, cornices, plasterboard, sidings, vents, tiles etc..

Gap Filla has good adhesion to: Glass, Ceramic, Wood, Brick, Metal, Concrete and many other substrates.

- **Paintable**
- **Water Clean up**
- **Flexible**
- **Adheres to most surfaces**

PROPERTY VALUE

Dynamic Movement 5% +/-
Tack Free (@25oC) 15 - 20 min
Cure Time @25oC 24 - 48 Hrs

LIMITATIONS

Adheseal Gap Filla is not recommended for water immersion or for use in chemical environments. It is also not suitable for food contact or high temperature applications. (i.e. Stoves, Fireplaces etc.)

SAFETY

Eye protection is recommended. In case of contact flush with water for 15 minutes; If irritation persists seek medical attention.

Remove contact lenses before use
Do not handle lenses until all traces are removed from hands and nails.

Keep out of the reach of children.

PACKAGING

300ml Cartridges 20 per carton
Store above 10oC and below 35oC

SHELF LIFE

Minimum 24 months

Physical Properties

Type of product	Acrylic Polymer
Curing system	Water Evaporation
Density (specific gravity)	1.50
Consistency	Smooth Paste
Application temperature	+5°C to +35°C
Storage: Cool Dry between	10°C and 35°C
VOC	22gm/Lt (Californian South Coast Air Quality Management Rule 1168)
Shelf life	12 month in original packaging
Clean up	Water
Colour	White

Safety:

This product is not classified as hazardous according to Work safe Australia however skin irritation and sensitisation may occur in sensitive individuals. Please consult M.S.D.S. for this product for further information.

Guarantee / Warranty:

We warrant our products to be free of defects and manufactured to rigid quality control specification. As it is impossible to control the use and application of the products, the company's liability is limited to replacing such quantities of product as are proven to be defective. The company disclaims any claims for repainting or other labour resulting from the use of the product. No responsibility is assumed for consequential damages arising from the use of the product. All other warranties including (merchantability or fitness for a particular purpose) are excluded. No representative of the company is authorised to grant any warranty or waive this limitation of liability. All claims concerning product defects must be made within twelve months of shipment. Absence of such claim in writing during this period will constitute a waiver of all such claims with respect to such product.

Adequate Tests:

The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendation and suggestion contained herein are made without guarantee or representation as to the results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your requirements.