

Technical Data Sheet

Primer 2001

Clear Primer

Adheseal
The Adhesive and Sealant Specialists

Description:

Primer 2001 is a solvent-based reactive primer. This primer is designed to improve adhesion on porous surfaces and as a rust inhibitor for automotive glass replacement.

Typical Uses:

Primer 2001 is used to enhance the adhesion of Polyurethanes and Hybrids on porous surfaces such as timber and masonry. When used on metals Primer 2001 will inhibit rust that may occur when the coating has been scratched in such instances like windscreen replacement.

Application:

Apply by means of brush or clean cloth at 50-150ml per square meter. Depending on surface porosity.

Cleaning:

Before dry clean with acetone or xylene.

After cured mechanical means is necessary.

Type of product	Polyurethane
Curing system	Air drying
Density (specific gravity)	1
Consistency	Liquid
Viscosity: Ford cup #4	15 seconds @20 degree Celsius
Application temperature	10-35 degree Celsius
Storage: Cool Dry between	10-35 degree Celsius
Consumption	50-150ml per square meter
VOC	
Shelf life	12 months
Clean up	Acetone
Colour	Clear/ yellowish

Safety

This product is not classified as hazardous according to Work safe Australia however skin irritation and sensitisation may occur in sensitive individuals. Please consult M.S.D.S. for this product for further information.

Guarantee / Warranty

We warrant our products to be free of defects and manufactured to rigid quality control specification. As it is impossible to control the use and application of the products, the company's liability is limited to replacing such quantities of product as are proven to be defective. The company disclaims any claims for repainting or other labour resulting from the use of the product. No responsibility is assumed for consequential damages arising from the use of the product. All other warranties including (merchantability or fitness for a particular purpose) are excluded. No representative of the company is authorised to grant any warranty or waive this limitation of liability. All claims concerning product defects must be made within twelve months of shipment. Absence of such claim in writing during this period will constitute a waiver of all such claims with respect to such product.

Adequate Tests

The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendation and suggestion contained herein are made without guarantee or representation as to the results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your requirements.